


FICHE TECHNIQUE

PTFE coated glass fabric adhesive: 141AP

FABRIC PICTURE:



DESCRIPTION AND PROPERTIES:

141AP reference is a PTFE coated glass fabric support (Polytetrafluoroethylene) with and adhesive side (silicone polymer):

- ✓ Non-sticky very smooth and very good sliding coefficient
- ✓ Operating temperature resistance from -73°C to +260°C
- ✓ Self-extinguishing
- ✓ Excellent dimensional stability
- ✓ Temperature and pressure do not have any noticeable effect and no creep
- ✓ Tasteless and odorless. Ability to enter with food products.
- ✓ Excellent resistance to friction
- ✓ Thanks to its chemical inertness, PTFE is unassailable by any chemical product, except molten Sodium (Na) and Potassium (K), as well as products that attack glass.
- ✓ Water recovery less than 0.01 % after 24 hours.

PROPERTIES	VALUE	UNITY
Fabric thickness	0.35	mm
Nominal fabric weight	680	g/m²
PTFE percentage	57	%
Adhesion	6,20	N/5 cm
Total thickness (fabric + silicone adhesive)	0.40	mm
Temperature resistance	-73 / + 260	°C

Tél: +33 (0)1 69 88 14 30

Fax: +33 (0)1 69 84 73 38

Web: www.techniflon.com

Email: techniflon@techniflon.com